

**Amendments to the Claims:**

This listing of claims will replace all prior revisions and listings of claims in the subject application, and please amend the claims as follows:

1. (Currently Amended) Boom gate apparatus comprising:

- (i) a portable trolley having at least one support wheel and a housing supporting one or more traffic indicators;
- (ii) an elongate gate mounted to the portable ~~trolley~~body; and
- (iii) actuating means for moving the elongate gate from an upright non-operational position to a horizontal operational position characterized in that;
- (iv) said actuating means is controlled by a hand held controller or transmitter and said housing contains a microprocessor for receiving a signal from the hand held remote controller or remote control transmitter for control of the actuating means as well as control of traffic indicators.

2. (Original) Boom gate apparatus as claimed in claim 1 wherein the portable trolley has a single pair of wheels and a handle.

3. (Original) Boom gate apparatus as claimed in claim 1 wherein the elongate gate comprises a single elongate arm.

4. (Original) Boom gate apparatus as claimed in claim 1 wherein the actuating means is a drive motor coupled by a belt or chain drive to a pivot arm which is operatively connected to the elongate gate by connection means.

5. (Currently Amended) Boom gate apparatus as claimed in claim ~~1~~ 4 wherein the connection means is a connection sleeve or joint between the elongate gate and the pivot arm which is

releasably attached to the elongate gate.

6. (Original) Boom gate apparatus as claimed in claim 5 wherein the elongate gate is connected to the connection sleeve by a splined or keyway arrangement so that the elongate gate and connection sleeve may rotate in unison.
7. (Original) Boom gate apparatus as claimed in claim 4 wherein the elongate gate is oriented normal to the pivot arm.
8. (Previously Presented) Boom gate apparatus as claimed in claim 4, wherein the drive motor is an electric motor powered by one or more batteries.
9. (Previously Presented) Boom gate apparatus as claim in claim 1 wherein the mobile trolley has a housing for the actuating means wherein in said housing there is located a receiver which receives a signal from the hand held controller or transmitter.
10. (Original) Boom gate apparatus as claimed in claim 9 wherein the signal is IR or RF.
11. (Original) Boom gate apparatus as claimed in claim 10 wherein the hand held controller is IR and the receiver is IR.
12. (Original) Boom gate apparatus as claimed in claim 11 wherein the housing has a transparent window located in an external wall thereof for transmission of the IR signal.
13. (Original) Boom gate apparatus as claimed in claim 11 wherein the housing includes an IR receiver which transmits a signal to an RF receiver in the housing which sends a signal to a microprocessor which actuates the drive motor.

14. (Previously Presented) Boom gate apparatus as claimed in claim 1 wherein there is provided a traffic indicator adjacent the elongate gate for indicating:

- (i) when traffic is free to pass through the elongate gate when in an elevated non-operational position; and
- (ii) when traffic is blocked from passing through the elongate gate when lowered to an operational position.

15. (Original) Boom gate apparatus as claimed in claim 14 wherein said traffic indicator includes a green light for position (i) and a red light for position (ii).

16 -17. (Cancelled)

18. (Original) A method of operation of boom gate apparatus as claimed in claim 1 which includes the steps of:

- (a) lowering the elongate gate by remote control using the hand held transmitter or controller to prevent passage of traffic along a roadway or lane of a roadway which said boom gate apparatus is located adjacent thereto;
- (b) permitting one or more persons to cross the lane or roadway while the elongate gate is in the lowered position; and
- (c) elevating the elongate gate to permit traffic along the roadway or lane when said one or more persons have crossed the roadway or lane.

19. (Original) A method as claimed in claim 18 wherein in step (a) and/or (b) a red light is flashing or other visual or audible indicator to indicate traffic should stop.

20. (Original) A method as claimed in claim 18 wherein in step (c) a green light is flashing or other visual or audible indicator to indicate traffic is free to pass along the roadway or lane previously blocked by the elongate gate.

Application No.: 10/582,806  
Office Action dated September 11, 2008  
Amendment and Response dated January 8, 2009  
Docket No.: 1567-6 PCT/US  
Page 5

21. (Original) A method claimed in claim 18 wherein a pair of said boom gate apparatus is used to block adjacent lanes of a roadway for traffic and steps (a), (b) and (c) are carried out simultaneously by each boom gate apparatus.
22. (New) Boom gate apparatus as claimed in claim 1, wherein the hand held remote controller or remote control transmitter has separate actuation buttons for controlling movement of the elongate gate and controlling operation of said one or more traffic indicators.
23. (New) Boom gate apparatus as claimed in claim 23, wherein actuation of the hand held remote controller or remote control transmitter also initiates a buzzer sound simultaneous with green light(s) indicating that it is safe to pass through the boom gate apparatus when the elongate gate is in the upright non-operational position.